





# AF150L LED Pole Light

The AF150L features a high performance LED fixture designed for automotive outdoor lighting. Compare the AF150L to 400 WATTS metal halide.



AF150L	
	90-277V STANDARD (480V OPTIONAL)
	150 WATTS
	21,000 LM <span style="float: right;">140 LM/W</span>
	5,000K CCT Optional 3000/4000 83 CRI
	23" x 17" x 3"
	100,000 L70 HOURS <span style="float: right;">IP65</span>
	Dark Bronze, White
	26 Lbs 11.7 KG
	Five Year Warranty Ten Year Optional



Model # AF100



ETL Intertek



83 CRI  
TrueColor  
Technology



Amerlight's  
LED Brightest  
in the Industry



Wireless  
Controls  
Available

Designed and Assembled in the USA



**AMERLIGHT**  
Advanced LED Technology

amerlight.com  
2800 Lynch Road Suite B  
Evansville, IN 47711



1 5/8" - 2 3/8" to Pole Mounting Diameter

360 degree rotation

Adjustable knuckle rotate 180 degrees

Optics:  
Type 3 Long for long forward throw  
Type 2  
Type 5 60 degree spot light

MORE LIGHT



## Installation

INSTALLATION – Die-cast aluminum arm with integral splice compartment. Standard arm is 4" in length. Aluminum fitter for 4" to 6" OD poles. 2.5 inch mounting diameter size with 2 hex head set bolts. Mounting knuckle rotate/tilts 180 degrees.

ELECTRIC - 14 AWG stranded wire with wire caps

CONSTRUCTION – Heavy gauge die-cast aluminum housing. Integral structural support plate for mounting arm and electrical components ensures rigidity and strength. Hinged aluminum door frame incorporates stainless steel hardware. Continuous silicone gasket surrounds lens for weather-tight seal. Lens: Thermal shock resistant tempered glass lens. Standard fixture colors; Dark Bronze, White, Light Gray. High gloss plastic coated. Custom colors available on special order.