



Description

The LN150 has a modular design with excellent heat dissipation and anti-corrosion capacity. Available with three different beam angles, flexible tool less entry for easy driver access, and three mounting options. This product is designed for indoor applications.



Certification

UL / DLC



Specifications

Part No.:	LN150
Wattage:	150 W
Lumens per Watt:	150 LM/W
Lumens:	22,500 LM
Input Voltage:	100V - 277V 200V - 480V Optional
Lens Options:	120°, 90°, 50x90°
CCT:	5000K
CRI:	80+
Dimensions:	22.7" x 10" x 2.3"
Dimmable:	1-10 V
Warranty:	5 Year Warranty
Mounting:	Hanging Kit Included Surface Mount or 3/4" NPT Pendant Optional
Options:	PIR Sensor Emergency Battery Backup RELOC® Modular Wiring Solutions



Mounting Options




Wire Hanging


Angle Brackets for Surface Mounting

3/4" NPT Pendant Mount for Conduit


Beam Angles



50X90°



90°



120°

Installation

1. Use a qualified electrical contractor and follow all applicable electrical codes.
2. Attach aircraft hanger wire to the joist or other secure mounting location.
3. Adjust length of wire to achieve the required height and angle from the floor.
4. Properly secure the wire.
5. Please insure that hanger wire meets all local seismic applicable codes.

Designed and Assembled in the USA

